

Revision Date: Oct 17, 2023

STANDARD FEATURES & SPECIFICATIONS Mansura Single Sections - 16', 18' & 20'



	General Construction
Building Code	A-277 Zone 7A*
Snow Load	Live load 42 psf (2.01 kPa)
	Ground snow load 72.6 psf (3.48 kPa)
Insulation R Values	Floors R-48, Walls R-22 & Ceiling R-40 (min)
	Meets zone 8 of the 9.36 Energy Code**
Floor	2"x10" floor joists @ 16" o.c.
	Heavy tubular steel frame w/detachable hitch
Decking	19/32" T & G OSB floor decking; glued and
	screwed
Roof	4/12 roof pitch; engineered roof trusses
	7/16" roof sheathing
	Architectural asphalt shingles -
	limited lifetime warranty
Eaves	12" sides, 18" front & rear vented eaves
Siding	Maintenance free vinyl lap siding & corners
Fascia	Coloured metal
Soffit	White vinyl
Building Envelope	Meets 0.20 L/M2S
Exterior Walls	2"x6", 24" o.c.
	3/8" OSB sheathing inside & outside of wall
Interior Walls	2"x4" Interior walls
	8' ceilings
	Cathedral ceiling in living, dining, and kitchen
Ceiling	Textured (primed) gyproc ceiling
Windows	1.36 U-value, dual low E argon filled PVC
	(meets zone 8 of the 9.36 Energy Code)*
	c/w vinyl sills, screens and security locks
	72x60v - Sliding
	46x42v - Sliding
	46x42v - Sliding
Kitchen (most models)	
Family Room (if app.)	60x60v - Sliding
Exterior Doors	36" Decorative insulated entry doors
	- front & rear
	Includes deadbolt & peephole
	Single lever door handle - satin nickel
	Coach lights at all exterior entrances
	Pot light ILO coach light at porch entrances
Exterior Decorative	Dormer over living room window
Features	Caspian columns at living room dormer

<u>Tasteful Interiors</u>		
Flooring	Carpet in living room, family room, den and	
	all bedrooms	
	Hallways: carpet in 18' & 20' wides (most	
	models); lino in 16' wides	
	Quality linoleum flooring all other areas	
Blinds	Cellular cordless blinds (excl bathrooms)	
Interior Doors	Conmore passage doors - white	
	Louvered bifold at furnace location - white	
Interior Door Handles	Single lever in satin nickel	
	Privacy locks on bathroom doors excluding	
	ensuites. If bathroom is an ensuite, bdrm door	
	will have privacy set.	
Closets	Solid white shelving	
Wall Finish	Decorative 1/2" vinyl on gyproc (VOG)	
	Battens on joints	
Moulding ¹	Vinyl wrapped	
	Matches cabinet colour (excl white)	
Windows & Doors	#3007 (2-1/4")	
Ceiling	Flat #3007 (2-1/4"); Vault #451 (2-5/8")	
Baseboards	#3007 (2-1/4")	
Electrical	Decora switches & recepts - white	
Lighting	Ceiling mount in all bdrms, halls & utility room	
	Decorative chandelier in dining room - chrome	
	Wired for ceiling fan in living room (2 switches)	

Bright, Beautiful Kitchens	
Tile	Single row w/metal tile edging
Range	30" electric - white
	Exterior vented range hood w/light - white
Fridge	19 cu.ft., 2-door, frost free - white
	Opening: 34"x73"
Sink	Double stainless steel sink
	Single lever faucet w/veggie sprayer - chrome
Pantry	Most models
Cabinets	Doweled, full modular cabinetry
	Cabinet crown moulding
	Five distinctive colors of cabinet doors
	Stepped cabinet over fridge & range
Countertop	Arborite
Lighting	Pot lights (x5)

Spacious Baths		
Tile	Single row w/metal tile edging	
Fixtures	One-piece quality fiberglass tub & shower	
	units	
	White oval drop in sink	
	Single flush toilet	
Faucets	Dual handle vanity faucets	
	Single lever faucet on tub/shower unit	
Hardware	Curved Shower rods in all tubs	
	Towel bar, ring & paper holder - chrome	
Vanity	Expansive vanity mirrors	
Countertop Heights:	32" in main & secondary bathrooms	
	36" in ensuite	
Electrical	GFI receptacle	
	Power bath fan(s)	
Lighting	Hampton light fixture	

Utility Services	
Electrical Service	100 amp
Heating	High efficiency (95+AFUE) single stage
	furnace
	Natural gas / propane
	Programmable thermostat
Water Heater	33 lmp. (40 US) gallon natural gas
	3m Insulated water lines on hot & cold
Washer / Dryer	Plumbed, wired & vented for side by side
	Solid shelf above washer/dryer location
Electrical - Other	Primary exhaust fan w/dehumidistat & switch
	Smoke detectors w/battery backup in bdrms
	CO/Smoke Detector(s) w/battery backup
	locations as per code
	Arc fault protection as required by code
	GFI protected receptacle for heat tape
	Dedicated receptacle in "Freezer Area"
	Exterior GFI electrical outlet by front door
	Blank communication outlet: kitchen (1),
	master bdrm (1)
Plumbing - Other	Exterior frost free water tap
	Shut off valves all fixtures (excl tubs)

reserve sizes & ¹N

In a continued effort to meet the challenges of product improvements, we reserve the right to modify plans, specifications & features without notice. Room sizes & square footage measurements are approximate.

**ADDITIONAL PROVINCIAL REQUIREMENTS MAY BE REQUIRED OUTSIDE OF AB & SASK

*ENERGY ZONE UPGRADES MAY BE REQUIRED BASED ON DESTINATION

PRICES DO NOT INCLUDE ASSOCIATION OR WARRANTY FEES

*DESIGNED TO MEET ZONE 7A IN AB & SASK ONLY