

## STANDARD FEATURES & SPECIFICATIONS Legacy Multi Sections



General Construction		Tasteful Interiors		Spacious Baths	
Building Code	A-277 Zone 7A*	Flooring	Carpet in living room, all bedrooms	Tile	Single row
Snow Load	Live load 42 psf (2.01 kPa)		and hallways	Fixtures	One-piece quality fiberglass oval tub &
	Ground snow load 72.6 psf (3.48 kPa)		Quality linoleum flooring all other areas		shower unit - ensuite
Insulation R Values	Floors R-40, Walls R-22 & Ceiling R-46 (min)	Blinds	Cellular cordless blinds (excl bathrooms)		One-piece quality fiberglass tub & shower
	Meets zone 8 of the 9.36 Energy Code**	Interior Doors	Pre-finished interior doors in Crystal		unit - main bath
Floor	2"x10" floor joists @ 16" o.c.		White colour		36" shower stall w/sliding glass doors (model
	Heavy tubular steel frame w/detachable hitch	Interior Door Handles	Round door knob - satin nickel		30404 only)
Decking	19/32" T & G OSB floor decking; glued and		Privacy locks on bathroom doors excluding		White oval drop in sink
	screwed		ensuites. If bathroom is an ensuite, bdrm door		Single flush toilet
Roof	4/12 roof pitch; hinged roof trusses		will have privacy set.	Faucets	Dual handle vanity faucets
	(Fixed roof available with truss floor option on 30'	Closets	Solid white shelving		Single lever faucet on tub/shower unit
	wides or less, may require overheight permit)	Wall Finish	Decorative 1/2" vinyl on gyproc (VOG)	Hardware	Curved Shower rods in all tubs
	7/16" roof sheathing		Battens on joints		Towel bar, ring & paper holder - chrome
	Architectural asphalt shingles -	Moulding <sup>1</sup>	Vinyl wrapped	Vanity	Expansive vanity mirrors
	limited lifetime warranty		Colour - Décor Specific	Countertop Heights:	32" in all bathrooms
Eaves	18" vented eaves all 4 sides	Windows & Doors	#3007 (2-1/4")	Electrical	GFI receptacle
Siding	Maintenance free vinyl lap siding & corners	Ceiling	Flat #161 (1-3/16"); Vault #3000 (1-5/8")		Power bath fan(s)
Weather Protection	White house wrap	Baseboards	#215 (1-1/2")	Lighting	Hampton light fixture
Fascia	Coloured metal	Electrical	Decora switches & recepts - white		· · · · · · · · · · · · · · · · · · ·
Soffit	White vinyl	Lighting	Ceiling mount in all bdrms, halls & utility room		Utility Services
Building Envelope	Meets 0.20 L/M2S		Decorative chandelier in dining room - chrome	Electrical Service	100 amp
Exterior Walls	2"x6", 24" o.c.			Heating	High efficiency (95+AFUE) single stage
	3/8" OSB sheathing inside & outside of wall	B	right, Beautiful Kitchens		furnace
	Shipping wall included on T/S models	Tile	Single row		Natural gas / propane
Interior Walls	2"x4" Interior walls	Range	30" electric - white		Programmable thermostat
	8' ceilings		Range hood w/light - white	Water Heater	39 Imp. (45 US) gallon electric
	Cathedral ceiling in living, dining, and kitchen	Fridge	19 cu.ft., 2-door, frost free - white		3m Insulated water lines on hot & cold
Ceiling	Textured (primed) gyproc ceiling		Opening: 34" x 69-3/4"	Washer / Dryer	Plumbed, wired & vented for washer/dryer
Windows	1.36 U-value, dual low E argon filled PVC	Sink	Double stainless steel sink		Solid shelf above washer/dryer location
	(meets zone 8 of the 9.36 Energy Code)*		Dual handle faucet - chrome	Electrical - Other	Primary exhaust fan w/dehumidistat & switch
	c/w vinyl sills, screens and security locks	Spacious Pantry	Selected models		Smoke detectors w/battery backup in bdrms
	72x60v - Sliding	Cabinets	Doweled, full modular cabinetry		CO/Smoke Detector(s) w/battery backup
Dining Room 46x42v - Sliding			Cabinet crown moulding		locations as per code
	46x42v - Sliding		Five distinctive colors of cabinet doors		Arc fault protection as required by code
Kitchen (most models)	36x36v - Sliding	Countertop	Arborite		GFI protected receptacle for heat tape
Family Room (if app.)	46x42v - Sliding	Lighting	Ceiling mount		Dedicated receptacle in "Freezer Area"
Exterior Doors	36" Decorative insulated entry door - Front		·		Exterior GFI electrical outlet by front door
		In a continued effort to meet the challenges of product improvements, we reserve the			
	32" Decorative insulated entry door - Rear	In a continued effort to mee	t the challenges of product improvements, we reserve the		Blank communication outlet in kitchen
	32" Decorative insulated entry door - Rear Includes deadbolt & peephole	right to modify plans, spec	ifications & features without notice. Room sizes & square	Plumbing - Other	Blank communication outlet in kitchen Exterior frost free water tap
	,	right to modify plans, spec		Plumbing - Other	
	Includes deadbolt & peephole	right to modify plans, spec	ifications & features without notice. Room sizes & square	Plumbing - Other	
	Includes deadbolt & peephole Round door knob - satin nickel	right to modify plans, spec. foota	ifications & features without notice. Room sizes & square		Exterior frost free water tap

<sup>1</sup>MOULDING SIZES IN CLOSETS / PANTRY / LINENS MAY BE DIFFERENT FROM LISTED SIZES

ALL PRICES FOB MEDICINE HAT

PRICES DO NOT INCLUDE ASSOCIATION OR WARRANTY FEES

Revision Date: MAY 23, 2024