

Revision Date: Mar 3, 2025

## **STANDARD FEATURES & SPECIFICATIONS**



General Construction		
Building Code	A-277 Zone 7A*	
Snow Load	Live load 42 psf (2.01 kPa)	
	Ground snow load 72.6 psf (3.48 kPa)	
Insulation R Values	Floors R-48, Walls R-22 & Ceiling R-40 (min)	
	Meets zone 8 of the 9.36 Energy Code**	
Floor	Engineered open web truss @ 19.2" o.c.	
	Double LVL rim board	
	(Home must be hauled on floats. Full length of	
	floor must be fully supported during transport.)	
Decking	19/32" T & G OSB floor decking; glued and	
· ·	screwed	
Roof	4/12 roof pitch; engineered roof trusses	
	7/16" roof sheathing	
	Architectural asphalt shingles -	
	limited lifetime warranty	
Eaves	16" vented eaves all 4 sides	
Sidina	Maintenance free vinyl lap siding & corners	
Fascia	Metal - white or black	
Soffit	White vinyl	
Building Envelope	Meets 0.20 L/M2S	
Exterior Walls	2"x6". 24" o.c.	
Exterior Walle	3/8" OSB sheathing inside & outside of wall	
Interior Walls	2"x4" Interior walls	
Interior Walls	8' ceilings	
	Cathedral ceiling in living, dining, and kitchen	
Ceiling	Textured (primed) gyproc ceiling	
Windows	1.36 U-value, dual low E argon filled PVC	
· · · · · · · · · · · · · · · · · · ·	(meets zone 8 of the 9.36 Energy Code)*	
	c/w vinyl sills, screens and security locks	
Living Room	72x60v - Sliding	
	46x42v - Sliding	
	46x42v - Sliding	
Kitchen (most models)		
Family Room (if app.)		
Exterior Doors	36" Decorative insulated entry doors	
	- front & rear	
	Includes deadbolt & peephole	
	Single lever door handle - satin nickel	
	Pot light at all exterior entrances	
Exterior Decorative	Dormer over living room window	
Features	Caspian columns at living room dormer	
i cataros	Caspian columns at living room domiel	

Tasteful Interiors		
Flooring	Quality linoleum flooring throughout	
Blinds	Cellular cordless blinds (excl bathrooms)	
Interior Doors	Conmore passage doors - white	
	Louvered bifold at furnace location - white	
Interior Door Handles	Single lever in satin nickel	
	Privacy locks on bathroom doors excluding	
	ensuites. If bathroom is an ensuite, bdrm door	
	will have privacy set.	
Closets	Solid white shelving	
Wall Finish	Decorative 1/2" vinyl on gyproc (VOG)	
	Battens on joints	
Moulding <sup>1</sup>	Vinyl wrapped	
	Colour - décor specific	
Windows & Doors #3007 (2-1/4")		
Ceiling	Flat #3007 (2-1/4"); Vault #451 (2-5/8")	
Baseboards	#3007 (2-1/4")	
Electrical	Decora switches & recepts - white	
Lighting	Ceiling mount in all bdrms, halls & utility room	
	Decorative chandelier in dining room - chrome	
	Wired for ceiling fan in living room (2 switches)	

Bright, Beautiful Kitchens	
Tile	Single row w/metal tile edging
Range	30" electric - white
	Range hood w/light - white
Fridge	19 cu.ft., 2-door, frost free - white
	Opening: 34"x73"
Sink	Double stainless steel sink
	Single lever faucet w/veggie sprayer - chrome
Pantry	Most models
Cabinets	Doweled, full modular cabinetry
	Cabinet crown moulding
	Five distinctive colors of cabinet doors
	Stepped cabinet over fridge & range
	Large island standard (most models)
Countertop	Arborite
Lighting	Pot lights (x5)

In a continued effort to meet the challenges of product improvements, we reserve
the right to modify plans, specifications & features without notice. Room sizes &
square footage measurements are approximate.

Spacious Baths		
Tile	Single row w/metal tile edging	
Fixtures	One-piece quality fiberglass oval tub &	
	shower unit - ensuite	
	Two-sided duma wall shower - ensuite	
	bathroom - select models	
	One-piece quality fiberglass tub & shower	
	unit - main bath	
	White oval drop in sink	
	Single flush toilet	
Faucets	Dual handle vanity faucets	
	Single lever faucet on tub/shower unit	
Hardware	Curved Shower rods in all tubs	
	Towel bar, ring & paper holder - chrome	
Vanity	Expansive vanity mirrors	
Countertop Heights:	32" in main & secondary bathrooms	
	36" in ensuite	
Electrical	GFI receptacle	
	Power bath fan(s)	
Lighting	Hampton light fixture	

<u>Utility Services</u>		
Electrical Service	100 amp	
Heating	High efficiency (95+AFUE) single stage	
	furnace	
	Natural gas / propane	
	Programmable thermostat	
Water Heater	33 lmp. (40 US) gallon natural gas	
	3m Insulated water lines on hot & cold	
Washer / Dryer	Plumbed, wired & vented for side by side	
	Recessed dryer outlet	
	Solid shelf above washer/dryer location	
Electrical - Other	Primary exhaust fan w/dehumidistat & switch	
	Smoke detectors w/battery backup in bdrms	
	CO/Smoke Detector(s) w/battery backup	
	locations as per code	
	Arc fault protection as required by code	
	GFI protected receptacle for heat tape	
	Dedicated receptacle in "Freezer Area"	
	Exterior GFI electrical outlet (2)	
	Blank communication outlet: living room (1),	
	master bdrm (1)	
Plumbing - Other	Exterior frost free water tap	
1	Shut off valves all fixtures (excl tubs)	

\*DESIGNED TO MEET ZONE 7A IN AB

\*ENERGY ZONE UPGRADES MAY BE REQUIRED BASED ON DESTINATION

\*\*ADDITIONAL PROVINCIAL REQUIREMENTS MAY BE REQUIRED OUTSIDE OF AB 1MOULDING SIZES IN CLOSETS / PANTRY / LINENS MAY BE DIFFERENT FROM LISTED SIZES

ALL PRICES FOB MEDICINE HAT PRICES DO NOT INCLUDE ASSOCIATION OR WARRANTY FEES