

SINGLE SECTION HOMES





CANADIAN BUILT



STANDARD FEATURES & SPECIFICATIONS

General Construction		
Building Code	A-277 Zone 7A*	
Snow Load	Live load 42 psf (2.01 kPa)	
	Ground snow load 72.6 psf (3.48 kPa)	
Insulation R Values	Floors R-40, Walls R-22 & Ceiling R-40 (min)	
	Meets zone 8 of the 9.36 Energy Code**	
Floor	2"x10" floor joists @ 16" o.c. (16' wides)	
	2"x12" floor joists @ 16" o.c. (20' wides)	
	Heavy tubular steel frame w/detachable hitch	
Decking	19/32" T & G OSB floor decking; glued and	
	screwed	
Roof	4/12 roof pitch; engineered roof trusses	
	7/16" roof sheathing	
	Architectural asphalt shingles -	
	limited lifetime warranty	
Eaves	18" front vented eaves (no side or rear eaves)	
Siding	Maintenance free vinyl lap siding & corners	
Weather Protection	White house wrap	
Fascia	Metal - white or black	
Soffit	White vinyl	
Building Envelope	Meets 0.20 L/M2S	
Exterior Walls	2"x6", 24" o.c.	
	3/8" OSB sheathing inside & outside of wall	
Interior Walls	2"x4" Interior walls	
	8' Flat ceilings	
Ceiling	Textured (primed) gyproc ceiling	
Windows	1.36 U-value, dual low E argon filled PVC	
	(meets zone 8 of the 9.36 Energy Code)*	
	c/w vinyl sills, screens and security locks	
Living Room	72x60v - Sliding (20' wides)	
	60x60v - Sliding (16' wides or less)	
	46x42v - Sliding	
	46x42v - Sliding	
Kitchen (most models)		
Exterior Doors	32" Decorative insulated entry doors	
	- front & rear	
	Includes deadbolt & peephole	
	Round door knob - satin nickel	
	Coach light at all exterior entrances	

<u>Utility Services</u>		
Electrical Service	100 amp	
Heating	High efficiency (95+AFUE) single stage	
	furnace	
	Natural gas / propane	
	Programmable thermostat	
Water Heater	33 Imp. (40 US) gallon electric HWT	
	3m Insulated water lines on hot & cold	
Washer / Dryer	Plumbed, wired & vented for side by side	
	Recessed dryer outlet	
Electrical - Other	Primary exhaust fan w/dehumidistat & switch	
	Smoke detectors w/battery backup in bdrms	
	CO/Smoke Detector(s) w/battery backup	
	locations as per code	
	Arc fault protection as required by code	
	GFI protected receptacle for heat tape	
	Exterior GFI electrical outlet (2)	
	Blank communication outlet - living room	

Tasteful Interiors	
Flooring	Carpet in living room, all bdrms & hallways
	in 20' wides (lino in hallways of 16' wides)
	Quality linoleum flooring all other areas
Interior Doors	Pre-finished interior passage doors in Crystal
	White colour
Interior Door Handles	Round door knob - satin nickel
	Privacy locks on bathroom doors excluding
	ensuites. If bathroom is an ensuite, bdrm door
	will have privacy set.
Closets	Solid white shelving
Wall Finish	Covered gyproc throughout
Moulding ¹	Vinyl wrapped
	Colour - Décor Specific
Windows & Doors	#3007 (2-1/4")
Ceiling	Flat #215 (1-1/2"); Opt Vault #3000 (1-5/8")
Baseboards	#215 (1-1/2")
Electrical	Switched receptacles in bedrooms
Lighting	Ceiling mount in halls & utility room
	Ceiling mount in dining room
	Note: No lights in bdrms

Bright, Beautiful Kitchens		
Tile	Single row	
Range Hood	Range hood w/light - white	
Fridge	Opening: 34" x 69-3/4"	
Sink	Double stainless steel sink	
	Dual handle faucet - chrome	
Cabinets	Doweled, full modular cabinetry	
	Five distinctive colors of cabinet doors	
	Peninsula kitchen (20' wides only)	
Countertop	Arborite	
Lighting	Ceiling mount	

Spacious Baths	
Tile	Single row
Fixtures	One-piece quality fiberglass tub & shower
	units
	White oval drop in sink
	Single flush toilet
Faucets	Dual handle vanity faucets
	Single lever faucet on tub/shower unit
Vanity	Expansive vanity mirrors
Countertop Heights:	32" in main & ensuite
Electrical	GFI receptacle
	Exhaust fan(s)
Lighting	Ceiling mount





Kalimore

Model 16405 (Note: rendering shown on front cover)

3 Beds | 2 Baths 16' x 76' ~ 1,216 sq. ft.



Inverness Model 16411

3 Beds | 1 Bath 16' x 66' ~ 1,056 sq. ft.



Options shown in image: 9-Lite Front & Rear Doors, Dormer, Optional 72x60v Living Room Windows, Extended Eaves.





Kelowna Model 16422

2 Beds | 1 Bath 16' x 60' ~ 960 sq. ft.



Options shown in image: Painted Smartboard Window Trim, 9-Lite Front & Rear Doors, Dormer, Extended Eaves.





Jamaica Model 16426

3 Beds | 1 Bath 16' x 60' ~ 960 sq. ft.



Options shown in image: Painted Smartboard Window Trim, 9-Lite Front & Rear Doors, Dormer, Extended Eaves,



Kampala Model 16427

4 Beds | 1 Bath 16' x 60' ~ 960 sq. ft.





Nashville Model 20112

3 Beds | 2 Baths 20' x 76' ~ 1,520 sq. ft.



Options shown in image: Painted Smartboard Window Trim, 9-Lite Front & Rear Doors, Dormer, 46x10v Arctic Glass Window, 22x36v Bathroom Window, Extended Eaves.





Olympia Model 20115



3 Beds | 2 Baths 20' x 76' ~ 1,520 sq. ft.

Options shown in image: Painted Smartboard Window Trim, 9-Lite Front & Rear Doors, Dormer, Extended Eaves.



Orlando Model 20117

4 Beds | 2 Baths 20' x 76' ~ 1,520 sq. ft.



Options shown in image: Painted Smartboard Window Trim, 9-Lite Front & Rear Doors, Dormer, Extended Eaves.







CANADIAN BUILTSINCE 1970

Exterior Wall Construction

Best Standard in the Housing Industry!

2"X6" EXTERIOR WALLS CONSTRUCTED (
@ 24" O/C TO MAXIMIZE ENERGY
EFFICIENCY


R22 INSULATION WITH 6 MIL POLY (ZONES 6 TO 8 UNDER 9.36 ENERGY CODE)

3/8" STRUCTURAL INTERIOR OSB FOR THE STRONGEST WALL IN THE INDUSTRY

ALPHA GLUE TO MAXIMIZE STRENGTH AND 'MAINTAIN HOMES INTEGRITY

1/2" VINYL COVERED GYPROC FASTENED OSB USING ALPHA GLUE SYSTEM

3/8" STRUCTURAL EXTERIOR OSB FASTENED TO STUDS WITH SHEATHING STAPLES



"We surpass the competition!"









MODULINEMEDICINEHAT.COM