

STANDARD FEATURES & SPECIFICATIONS Lakehouse 20'



General Construction		Tasteful Interiors		Spacious Baths	
Building Code	A-277 Zone 7A*	Flooring	Plush Saxony Carpet in living room, halls and	Tile	Single row deluxe tile w/metal edging
Snow Load	Live load 42 psf (2.01 kPa)		all bedrooms	Fixtures	One-piece quality fiberglass tub & shower
	Ground snow load 72.6 psf (3.48 kPa)		Quality linoleum flooring all other areas		units
Insulation R Values	Floors R-40, Walls R-22 & Ceiling R-40 (min)	Blinds	2" Cellular cordless blinds (excl bathrooms)		White oval drop in sink
	Meets zone 8 of the 9.36 Energy Code**	Interior Doors	Pre-finished interior passage doors in Crystal		Single flush toilet
Floor	2"x12" floor joists @ 16" o.c.		White colour	Faucets	Dual handle vanity faucets
	Heavy tubular steel frame w/detachable hitch		Bifold at Washer/Dryer location (select		Single lever faucet on tub/shower unit
Decking	19/32" T & G OSB floor decking; glued and	Interior Door Handles	Round door knob - satin nickel	Hardware	Curved Shower rods in all tubs
	screwed		Privacy locks on bathroom doors excluding		Towel bar, ring & paper holder - chrome
Roof	4/12 roof pitch; engineered roof trusses		ensuites. If bathroom is an ensuite, bdrm door	Vanity	Expansive vanity mirrors
	7/16" roof sheathing		will have privacy set.	Countertop Heights:	32" in main
	Architectural asphalt shingles -	Closets	Solid white shelving		36" in ensuite
	limited lifetime warranty		Deluxe sliding bypass closet doors in	Electrical	GFI receptacle
Eaves	12" sides. 18" front vented eaves	†	master bedroom (select models only)		Power bath fan(s) on separate switch
Sidina	Maintenance free vinyl lap siding & corners	Wall Finish	Decorative 1/2" vinyl on gyproc (VOG)	Lighting	Hampton light fixture
Fascia	Metal - white or black		Battens on joints	gg	
Soffit	White vinyl	Moulding ¹	Vinyl wrapped, cathedral moulding throughout		Utility Services
Porch Features	Composite Deck Boards	moulding	Colour - décor specific	Electrical Service	100 amp
(select models)		Windows & Doors		Heating	High efficiency (95+AFUE) furnace with
Building Envelope	Meets 0.20 L/M2S		Vault #451 (2-5/8")	. iouung	variable 2 speed blower & A/C ready split
Exterior Walls	2"x6", 24" o.c.		#3007 (2-1/4")		Natural gas / propane
	3/8" OSB sheathing inside & outside of wall	Electrical	Decora switches & recepts - white		Dual Stage programmable thermostat
Interior Walls	2"x4" Interior walls	Lighting	Ceiling mount in all bdrms & halls	Water Heater	33 lmp. (40 US) gallon electric
	6 mil Interior vapour barrier	5 5	Decorative chandelier in dining room - chrome		3m Insulated water lines on hot & cold
Ceiling	8' Textured (primed) gyproc cathedral ceiling			Washer / Dryer	Plumbed, wired & vented for washer/dryer
Windows	1.36 U-value, dual low E argon filled PVC	Bright, Beautiful Kitchens		. ,	Recessed dryer outlet
	(meets zone 8 of the 9.36 Energy Code)*	Tile	Single row deluxe tile w/metal edging		Solid shelf above washer/dryer location
	c/w vinyl sills, screens and security locks	Range	30" easy clean electric - white	Electrical - Other	Primary exhaust fan w/dehumidistat & switch
Master Bedroom	46x42v - Sliding	5	Range hood w/light - white		Smoke detectors w/battery backup in bdrms
Secondary Bdrms		Fridge	19 cu.ft., 2-door, frost free - white		CO2/Smoke Detector(s) w/battery backup
Kitchen (most models)	36x36y - Sliding	5	Opening: 34"x73"		locations as per code
Front Porch Models:	5	Sink	Double stainless steel sink		Arc fault protection as required by code
Living Room	46x68v transom style - Sliding x 4		Dual handle faucet - chrome		GFI protected receptacle for heat tape
	46x68v transom style - Sliding	Pantry	Select models		Dedicated receptacle in "Freezer Area"
Front Bay Models:	, , ,	Cabinets	Doweled, full modular cabinetry		Exterior GFI electrical outlet (2)
	30x60v - Sliding x 2 & 36x60 - Picture x 3		Cabinet crown moulding		Blank communication outlet: living room (1),
	46x42v - Sliding		Five distinctive colors of cabinet doors		master bdrm (1)
Exterior Doors	36" 9 lite Front door (porch models only)	Countertop	Arborite	Plumbing - Other	Exterior frost free water tap
	32" Decorative insulated entry door - Rear	Lighting	Ceiling mount		······································
	Includes deadbolt & peephole				*DESIGNED TO MEET ZONE 7A IN AB
	Residential vinyl Patio Door (bay models only)	In a continued effort to mee	t the challenges of product improvements, we reserve the	*ENERG	Y ZONE UPGRADES MAY BE REQUIRED BASED ON DESTINATION
1					

In a continued effort to meet the challenges of product improvements, we reserve the right to modify plans, specifications & features without notice. Room sizes & square footage measurements are approximate.

**ADDITIONAL PROVINCIAL REQUIREMENTS MAY BE REQUIRED OUTSIDE OF AB

¹MOULDING SIZES IN CLOSETS / PANTRY / LINENS MAY BE DIFFERENT FROM LISTED SIZES

ALL PRICES FOB MEDICINE HAT

PRICES DO NOT INCLUDE ASSOCIATION OR WARRANTY FEES

Round door knob - satin nickel

Pot light at all exterior entrances